

GDR06

COMACCHIO GEO 405

TRACK MOUNTED · REMOTELY OPERATED



500_m

NQ

300_m

HQ

150_m

PQ

6.6_t

PULL BACK

OVERVIEW

Purpose-built for tight-access geotechnical, environmental and water well programs. Rubber-tracked and remotely operated for exceptional manoeuvrability and safe operation in challenging terrain.

Standard equipment includes an automatic SPT hammer, L09 bean pump, high-volume mono pump, two winches, and a twin breakout table with automatic rod breaker and casing extractor.

DEPTH CAPABILITY

NQ		500m
HQ		300m
Rotary mud		250m
Rotary air		250m
PQ		150m

Bars scaled to this rig's maximum rated depth (500 m). Depths are rated capability under favourable ground conditions.

FULL SPECIFICATION

ROTARY DRIVE HEAD	8 speed · 50–750rpm
PULL DOWN	4.6t
BREAKOUT TABLE	9.6t · twin hydraulic
DTH DRILLING	8 inch
SPT HAMMER	Automatic

HEAD WINCH LINES	2
PULL BACK	6.6t
DRILLING	Multipurpose
SAMPLING	Push tube
PUMPS	L09 bean · high-volume mono

SAFETY & COMPLIANCE

Mine compliant with up-to-date mine-spec safety features including fire suppression, remote and fixed emergency stops and isolators. Backed by a comprehensive HSE Management System and operated by qualified, experienced personnel.